




Optional



**MEMODERIVA**<sup>®</sup>  
MÁQUINAS & EQUIPAMENTOS INDUSTRIAIS

## Guilhotina CPN

	Comprim. de corte	Máximo Espessura	Angulo de corte	Número de pisadores	Altura da mesa	Gola de ganço	Comprim. Total	Largura Total	Altura Total	Potência Motor kW	Peso Kg	Topo Traseiro	Motor sup. Traseiro
CPN 4x2000	2100	4	1°30'	11	810	225	2650	1850	1680	5.5	3500	20-620	0,55
CPN 6x2000	2100	6	1°30'	11	810	225	2650	1850	1680	7.5	4000	20-620	0,55
CPN 10x2000	2100	10	1°40'	11	810	225	2650	1800	1850	11	5000	20-1000	0,55
CPN 13x2000	2100	13	2°	11	820	225	2700	2150	2100	18.5	7600	20-1000	0,55
CPN 16x2000	2100	16	2°30'	11	820	225	2700	2200	2150	18.5	8500	20-1000	0,55
CPN 20x2000	2100	20	3°	11	850	225	2720	2200	2250	22	12000	20-1000	0,55
CPN 6x3200	3200	6	1°30'	15	810	225	3850	1900	1680	7.5	6100	20-1000	0,55
CPN 8x3200	3200	8	1°30'	15	810	225	3850	1900	1680	7.5	6800	20-1000	0,55
CPN 10x3200	3200	10	1°40'	15	810	225	3900	2050	1850	11	8000	20-1000	0,55
CPN 12x3200	3200	13	2°	15	820	225	3950	2150	2050	18.5	9100	20-1000	0,55
CPN 16x3200	3200	16	2°30'	15	820	225	3950	2200	2150	18.5	10500	20-1000	0,55
CPN 20x3200	3200	20	3°	15	850	225	3950	2200	2250	37	16500	20-1000	0,55
CPN 25x3200	3200	25	3°30'	15	950	225	4000	2350	2350	45	19000	20-1000	0,55
CPN 6x4000	4100	6	1°30'	19	810	225	4300	2000	1750	7.5	7000	20-620	0,55
CPN 8x4000	4100	8	1°30'	19	810	225	4300	2000	1750	7.5	7600	20-1000	0,55
CPN 10x4000	4100	10	1°40'	19	810	225	4350	2100	2050	11	10000	20-1000	0,55
CPN 12x4000	4100	13	2°	19	820	225	4400	2250	2150	18.5	11600	20-1000	0,55
CPN 16x4000	4100	16	2°30'	19	820	225	4400	2250	2150	18.5	13600	20-1000	0,55
CPN 20x4000	4100	20	3°	19	950	225	4400	2350	2350	37	20000	20-1000	0,55
CPN 25x4000	4100	25	3°30'	19	1050	225	4450	2450	2550	45	24000	20-1000	0,55
CPN 6x6000	6100	6	1°30'	25	950	225	6350	2350	2050	11	16000	20-1000	0,55
CPN 8x6000	6100	8	1°30'	25	950	225	6350	2350	2050	15	18000	20-1000	0,55
CPN 10x6000	6100	10	1°40'	25	1000	225	6450	2450	2050	18.5	21000	20-1000	0,55
CPN 12x6000	6100	13	2°	25	1100	225	6500	2450	2650	22	26000	20-1000	0,55
CPN 16x6000	6100	16	2°30'	25	1100	225	6500	2500	2750	30	35000	20-1000	0,55
CPN 20x6000	6100	20	3°	25	1200	225	6550	2600	2900	45	45000	20-1000	0,55

Topo posterior por C.N. microcyber - Mesa com esferas rotativas - Braço com métrica - Iluminação linha de corte  
Regulador independente dos pisadores - Componentes hidráulicos, pneumáticos, eléctricos de marcas de qualidade

