

## Electric cylinder unit EPCS

**FESTO**



## Characteristics

### At a glance

Link [epcs](#)



The simplicity of pneumatics is now combined for the first time with the advantages of electric automation thanks to the Simplified Motion Series. These integrated drives are the perfect solution for users who are looking for an electric alternative for very simple motion and positioning tasks between two mechanical end positions, but don't want the commissioning process for traditional electric drive systems that can often be quite complex.


- No external servo drive: all necessary electronic components combined in the integrated drive
- Two control options integrated as standard: digital I/O and IO-Link®
- Complete solution for simple movements between mechanical end positions
- Simplified commissioning: all parameters can be manually set directly on the drive
- No special knowledge required for commissioning
- Minimal zero stroke and extremely compact design make this product the perfect choice for applications where space is at a premium
- Very high-quality ball screw with low internal friction
- Ideal for fast movement in sorting, distribution and testing applications

### Cylinder with guide unit

- For protecting the piston rod against rotation
- For precise movements

### Ordering data - modular system

Link [epcs](#)



### Configurable product

This product and all its product options can be ordered online via the configurator.

### Engineering tools

Link [engineering tools](#)

Save time with engineering tools: Smart engineering for the optimal solution. Our goal is to increase your productivity. Our engineering tools play an integral part in achieving this goal. They help you size your system correctly, tap into unimagined productivity reserves and generate additional productivity along the entire value chain. In every phase of your project, from the initial contact to the modernisation of your machine, you will come across a number of different tools that will be of use to you.

### Simplified Motion Series - Solution Finder

- Selection tool for simple electric drive solutions from the Simplified Motion Series: This Solution Finder makes finding solutions for electric motion tasks child's play. All you have to do is enter the main application parameters like stroke, payload and motion type, and the system suggests the best solution for your simple motion task in seconds. Then you can simply add it to your shopping basket with just one click and order it online.

### Diagrams

Link [epcs](#)



The diagrams shown in this document are also available online. These can be used to display precise values.

### Ball screw pitch

The spindle pitch describes the distance travelled by the spindle nut per revolution of the spindle in millimetres.

## Characteristics

### Position sensing

By using proximity switches, any position can be detected.

### Motor type


#### **IO-Link**

The motor is integrated into the drive and can be easily commissioned according to the “plug and work” principle. The relevant parameters can be set directly on the drive. Control is via digital I/O or IO-Link.

### Control panel

When aligning the motor, make sure that the buttons (for parameterisation and control) can be used.

[H1]      Integrated



### Bus protocol/activation

PNP or NPN switching outputs can be selected for actuation.


### End-position sensing

End position feedback similar to a conventional proximity switch, integrated as standard


### Cable outlet direction

Describes the alignment of the motor on the drive. Depending on the alignment, the connecting cables can be routed according to the customer's specifications. The cables are positioned at a 45° angle to the axis.


[]      Standard




[]      Underneath



[]      Left




[]      Right



## Characteristics


### Motor attachment position



### Electrical accessories

Connecting cable between the motor and IO-Link master

### Overview



- From the individual axis to the handling system, such as a cantilever system, planar surface gantry or three-dimensional gantry
- The toothed belt and spindle axes ELGC and mini slides EGSC form a scalable modular system for compact automation systems
- The common platform architecture provides an integrated range with matching interfaces. A large number of systems can be implemented completely without adapter plates
- High-performance drive and guide elements ensure a long service life as well as excellent load-bearing capacity and reliability
- The uniform and universal range of accessories reduces warehousing and design costs

## Type code

001	Series	
EPSC	Electric cylinder	
002	Drive system	
BS	Ball screw drive	
003	Size	
32	32	
45	45	
60	60	
004	Stroke [mm]	
25	25	
50	50	
75	75	
100	100	
125	125	
150	150	
175	175	
200	200	
250	250	
300	300	
350	350	
400	400	
500	500	
005	Ball screw pitch	
3P	3 mm	
5P	5 mm	
8P	8 mm	
10P	10 mm	
12P	12 mm	
006	Position sensing	
A	For proximity sensor	

007	Motor type	
ST	Stepper motor ST	
008	Controller	
M	Integrated	
009	Control panel	
H1	Integrated	
010	Bus protocol/activation	
PLK	PNP and IO-Link®	
NLK	NPN and IO-Link®	
011	End-position sensing	
AA	With integrated end-position sensing	
012	Cable outlet direction	
	Standard	
D	Underneath	
L	Left	
R	Right	
013	Motor attachment position	
	Standard	
PL	Parallel, left	
PR	Parallel, right	
PD	Parallel, bottom	
PT	Parallel, top	
014	Electrical accessories	
	None	
L1	Adapter for operation as IO-Link® device	

## Datasheet

## General technical data

Size	32	45	60
Design	Electric cylinder, With ball screw drive, With integrated drive		
Type of motor	Stepper motor		
Protection against torque/guide	With plain-bearing guide		
Piston-rod end	Male thread		
Piston rod thread	M8	M10x1.25	M12x1.25
Stroke	25 mm; 50 mm; 100 mm; 150 mm; 200 mm	25 mm; 50 mm; 100 mm; 150 mm; 200 mm; 250 mm; 300 mm	25 mm; 50 mm; 100 mm; 150 mm; 200 mm; 250 mm; 300 mm; 350 mm; 400 mm; 500 mm
Stroke reserve	0 mm		
Torsional backlash at piston rod +/-	1 deg		
Additional functions	User interface Integrated end-position sensing		
Display	LED		
Referencing	Positive fixed stop block Negative fixed stop block Reference switch		
Type of mounting	Via female thread With accessories		
Mounting position	optional		
Max. cable length	15 m outputs 15 m inputs 20 m with IO-Link® operation		

## Mechanical data

Size	32	45	60			
Spindle pitch	3	8	3	10	5	12
Spindle diameter	8 mm			10 mm		
Reference value effective load, horizontal	24 kg		60 kg	40 kg	120 kg	56 kg
Reference value effective load, vertical	12 kg	9 kg	23 kg	13 kg	46 kg	18 kg
Max. feed force Fx	150 N		450 N	250 N	900 N	375 N
Max. radial force at drive shaft	75 N		180 N		230 N	
Max. speed <sup>1)</sup>	0.079 m/s	0.21 m/s	0.074 m/s	0.23 m/s	0.09 m/s	0.22 m/s
Speed „Speed press“	0.01 m/s					
Max. acceleration <sup>2)</sup>	1.5 m/s <sup>2</sup>	5 m/s <sup>2</sup>	1.5 m/s <sup>2</sup>	5 m/s <sup>2</sup>	1.5 m/s <sup>2</sup>	5 m/s <sup>2</sup>
Repetition accuracy	±0.02 mm					
Reversing backlash theoretical <sup>3)</sup>	100 µm					
Position sensing	For proximity sensor					

1) Adjustable in steps of 10%.

2) Parameter cannot be changed.

For parallel kit:

EPSCS-...3P/5P: 0.5 m/s<sup>2</sup>EPSCS-...8P/10P/12P: 1.5 m/s<sup>2</sup>

3) In new condition.

## Spindle

Size	32	45	60
Spindle diameter	8 mm	10 mm	12 mm
Spindle pitch	3 ... 8 mm/U	3 ... 10 mm/U	5 ... 12 mm/U

## Datasheet

Electrical data			
Size	32	45	60
Nominal voltage DC	24 V		
Permissible voltage fluctuations	+/- 15%		
Nominal current	3 A		5.3 A
Max. current consumption	3 A		5.3 A
Max. current consumption, logic	0.3 A		
Rotor position sensor	Absolute single-turn encoder		
Rotor position sensor, encoder measuring principle	Magnetic		
Rotor position transducer resolution	16 bit		

Interfaces			
Size	32	45	60
Parameterisation interface	IO-Link, User interface		
Working range of logic input	24 V		
Number of digital logic inputs	2		
Features of logic input	Configurable Not galvanically isolated		
Switching logic for inputs	NPN (negative switching) PNP (positive switching)		
Specification logic input	Based on IEC 61131-2, type 1		
Max. current digital logic outputs	100 mA		
Number of digital logic outputs 24 V DC	2		
Features of digital logic outputs	Configurable Not galvanically isolated		
Switching logic for outputs	NPN (negative switching) PNP (positive switching)		

Technical data IO-Link®			
Size	32	45	60
IO-Link, SIO-Mode support	Yes		
IO-Link, communication mode	COM3 (230.4 kBaud)		
IO-Link, Port class	A		
IO-Link, Number of ports	1		
IO-Link, Process data length OUT	2 bytes		
IO-Link, Process data content OUT	Move in 1 bit Move out 1 bit Quit Error 1 bit Move intermediate 1 bit		
IO-Link, Process data length IN	2 bytes		
IO-Link, Process data content IN	State Device 1 bit State In 1 bit State Intermediate 1 bit State Move 1 bit State Out 1 bit		
IO-Link, Service data IN	32-bit force 32-bit position 32-bit speed		
IO-Link, Min. cycle time	1 ms		
IO-Link, Data storage required	0.5 KB		
IO-Link, Protocol version	Device V 1.1		

## Datasheet

## Operating and ambient conditions

Size	32	45	60
Ambient temperature	0 ... 50°C		
Storage temperature	-20 ... 60°C		
Note on ambient temperature	Power must be reduced by 2% per K at ambient temperatures above 30°C.		
Temperature monitoring	Switch-off for excessive temperature Integrated precise CMOS temperature sensor with analogue output		
Relative air humidity	0 - 90%, Non-condensing		
Insulation protection class	B		
Protection class	III		
Degree of protection	IP40		
Duty cycle	100%		
CE mark (see declaration of conformity) <sup>1)</sup>	To EU EMC Directive In accordance with EU RoHS Directive		
UKCA marking (see declaration of conformity) <sup>2)</sup>	To UK instructions for EMC To UK RoHS instructions		
KC mark	KC-EMV		
Approval	RCM trademark		
Vibration resistance	Transport application test with severity level 1 to FN 942017-4 and EN 60068-2-6		
Shock resistance	Shock test with severity level 1 to FN 942017-5 and EN 60068-2-27		
Cleanroom suitability, measured according to ISO 14644-14	Class 9 according to ISO 14644-1		
Maintenance interval	Life-time lubrication		

1) Further information [www.festo.com/catalogue/...](http://www.festo.com/catalogue/) → Support/Downloads.2) Further information [www.festo.com/catalogue/...](http://www.festo.com/catalogue/) → Support/Downloads.

## Weight

Size	32	45	60
Basic weight for 0 mm stroke <sup>1)</sup>	818 g, 982 g	1,185 g, 1,308 g	2,294 g, 2,558 g
Additional weight per 10 mm stroke	24 g	41 g	69 g
Moving mass for 0 mm stroke	98 g	179 g	305 g
Additional moving mass per 10 mm stroke	3.3 g	4.9 g	6.5 g


1) For axial motor mounting / for parallel motor mounting

## Materials

Size	32	45	60
Material housing	Smooth-anodised wrought aluminium alloy		
Material piston rod	High-alloy stainless steel		
Material spindle	Rolled steel		
Material ball screw nut	Steel		
LABS (PWIS) conformity	VDMA24364 zone III		
Note on materials	RoHS-compliant		

## Datasheet

## Max. permissible loads on the piston rod



Size	32	45	60			
Spindle pitch	3	8	3	10	5	12
Max. feed force Fx	150 N	450 N			250 N	900 N
Max. moment Mx	0 Nm					
Max. moment My	1.5 Nm	2.9 Nm			6.4 Nm	
Max. moment Mz	1.5 Nm	2.9 Nm			6.4 Nm	


## Calculation of the load comparison factor

$$f_v = \frac{|F_{y1}|}{F_{y2}} + \frac{|F_{z1}|}{F_{z2}} + \frac{|M_{x1}|}{M_{x2}} + \frac{|M_{y1}|}{M_{y2}} + \frac{|M_{z1}|}{M_{z2}} \leq 1$$

If the piston rod is subjected to two or more of the indicated forces and torques simultaneously, the following equation must be satisfied in addition to the indicated maximum loads.


F1 / M1 = dynamic value  
F2 / M2 = maximum value

## Max. permissible transverse forces F on the piston rod as a function of projection A



Note:  
Sizing software „Electric Motion Sizing“

## Datasheet

Piston rod deflection  $f$  as a function of cantilever load  $A$  and lateral force  $F$ Piston rod deflection  $f$  as a function of cantilever load  $A$  and transverse force  $F$ 

$$f_1 = \frac{F_1}{F_2} \cdot f_2$$

$f_1$  = Piston rod deflection caused by lateral force [mm]

$F_1$  = Lateral force [N]

$F_2$  = Standardised lateral force [N] (constant force from graph)

$f_2$  = Piston rod deflection caused by lateral force [N] (reading from graph)

Calculating the mean feed force  $F$  (to DIN 69051-4)

$$F_{xm} = \sqrt[3]{\sum F_x^3 \cdot \frac{v_x}{v_{xm}} \cdot \frac{q}{100}} =$$

$$F_{xm} = \sqrt[3]{F_{x1}^3 \cdot \frac{v_{x1}}{v_{xm}} \cdot \frac{q_1}{100} + F_{x2}^3 \cdot \frac{v_{x2}}{v_{xm}} \cdot \frac{q_2}{100} + F_{x3}^3 \cdot \frac{v_{x3}}{v_{xm}} \cdot \frac{q_3}{100} + \dots}$$

The peak feed force value must not exceed the maximum feed force within a movement cycle. The peak value is generally achieved in vertical operation during the acceleration phase of the upward stroke. If the maximum feed force is exceeded, this can increase wear and thus shorten the service life of the ball screw. The maximum speed must likewise not be exceeded.

During operation, the continuous feed force may be briefly exceeded up to the maximum feed force. However, the continuous feed force must be adhered to when averaged out over a movement cycle.

Mean feed speed  $v$  (according to DIN 69051-4)

$$v_{xm} = \bar{v} \quad v_x \cdot \frac{q}{100} = v_{x1} \cdot \frac{q_1}{100} + v_{x2} \cdot \frac{q_2}{100} + v_{x3} \cdot \frac{q_3}{100} + \dots$$

$F_x$  = feed force

$F_{xm}$  = mean feed force

$F_{x\max.}$  = max. feed force

$F_{x\text{continuous}}$  = continuous feed force

$q$  = time


$v_x$  = feed speed

$v_{xm}$  = mean feed speed

$v_{x\max.}$  = max. feed speed

## Datasheet


## Mean feed force F as a function of running performance L, at an operating coefficient of 1.0 and room temperature for EPCS-BS-32



## Note:

The specifications for the running performance are based on experimentally determined and theoretically calculated data (at room temperature). Under different parameters, the running performance that can be achieved in practice can deviate considerably from the specified characteristic curves.


## Mean feed force F as a function of running performance L, at an operating coefficient of 1.0 and room temperature for EPCS-BS-45



## Note:

The specifications for the running performance are based on experimentally determined and theoretically calculated data (at room temperature). Under different parameters, the running performance that can be achieved in practice can deviate considerably from the specified characteristic curves.

## Mean feed force F as a function of running performance L, at an operating coefficient of 1.0 and room temperature for EPCS-BS-60



## Note:

The specifications for the running performance are based on experimentally determined and theoretically calculated data (at room temperature). Under different parameters, the running performance that can be achieved in practice can deviate considerably from the specified characteristic curves.

## Datasheet

## Service life taking into account the operating coefficient


$$L_1 = \frac{L}{f_B^3}$$

Operating coefficient  $f_B$ 

- 1.0 ... 1.2 (for measuring machine)
- 1.2 ... 1.4 (for handling technology, robotics)
- 1.4 ... 1.6 (for press-fitting operations)
- 1.6 ... 2.0 (for construction, agriculture)

 $L_1$  = actual service life $L$  = target service life $f_B$  = operating coefficient

## Sizing example




Application data:

- Payload: 25 kg
- Mounting position: horizontal
- Motor mounting position: axial
- Stroke: 150 mm
- Max. permissible positioning time: 2 s (one direction)

Step 1:

Smallest possible size from the table "Mechanical data": EPCS-BS-45-10P



Step 2:


Selecting the max. speed level  $v$  for payload  $m$  (see diagram on the left)

Step 3:

Reading off the min. positioning time  $t$  for stroke  $l$  (see diagram on the left)

Result: The application can be realised with EPCS-BS-45-150-10P. A minimum positioning time (one direction) of 1 s is achieved.


Longer positioning times can be selected at any time using a lower speed level.

Mass  $m$  as a function of speed level  $v$ , with axial kit, horizontal mounting position for EPCS-BS-32-3P

Note:


The lines represent the maximum values. The lower speed levels can be set at any time.

## Datasheet

Mass  $m$  as a function of speed level  $v$ , with axial kit, horizontal mounting position for EPSCS-BS-32-8P


## Note:

The lines represent the maximum values. The lower speed levels can be set at any time.

Mass  $m$  as a function of speed level  $v$ , with axial kit, horizontal mounting position for EPSCS-BS-45-3P

## Note:

The lines represent the maximum values. The lower speed levels can be set at any time.


Mass  $m$  as a function of speed level  $v$ , with axial kit, horizontal mounting position for EPSCS-BS-45-10P

## Note:

The lines represent the maximum values. The lower speed levels can be set at any time.

## Datasheet


### Mass m as a function of speed level v, with axial kit, horizontal mounting position for EPCS-BS-60-5P



Note:

The lines represent the maximum values. The lower speed levels can be set at any time.


### Mass m as a function of speed level v, with axial kit, horizontal mounting position for EPCS-BS-60-12P



Note:

The lines represent the maximum values. The lower speed levels can be set at any time.


### Mass m as a function of speed level v with axial kit, vertical mounting position for EPCS-BS-32-3P



Note:


The lines represent the maximum values. The lower speed levels can be set at any time.

## Datasheet

Mass  $m$  as a function of speed level  $v$  with axial kit, vertical mounting position for EPSCS-BS-32-8P


## Note:

The lines represent the maximum values. The lower speed levels can be set at any time.

Mass  $m$  as a function of speed level  $v$  with axial kit, vertical mounting position for EPSCS-BS-45-3P

## Note:

The lines represent the maximum values. The lower speed levels can be set at any time.


Mass  $m$  as a function of speed level  $v$  with axial kit, vertical mounting position for EPSCS-BS-45-10P

## Note:

The lines represent the maximum values. The lower speed levels can be set at any time.

## Datasheet


### Mass m as a function of speed level v with axial kit, vertical mounting position for EPSCS-BS-60-5P



Note:

The lines represent the maximum values. The lower speed levels can be set at any time.


### Mass m as a function of speed level v with axial kit, vertical mounting position for EPSCS-BS-60-12P



Note:

The lines represent the maximum values. The lower speed levels can be set at any time.


### Mass m as a function of speed level v with parallel kit, horizontal mounting position for EPSCS-BS-32-3P



Note:


The lines represent the maximum values. The lower speed levels can be set at any time.

## Datasheet

Mass  $m$  as a function of speed level  $v$  with parallel kit, horizontal mounting position for EPSCS-BS-32-8P


## Note:

The lines represent the maximum values. The lower speed levels can be set at any time.

Mass  $m$  as a function of speed level  $v$  with parallel kit, horizontal mounting position for EPSCS-BS-45-3P

## Note:

The lines represent the maximum values. The lower speed levels can be set at any time.


Mass  $m$  as a function of speed level  $v$  with parallel kit, horizontal mounting position for EPSCS-BS-45-10P

## Note:

The lines represent the maximum values. The lower speed levels can be set at any time.

## Datasheet


### Mass m as a function of speed level v with parallel kit, horizontal mounting position for EPCS-BS-60-5P



Note:

The lines represent the maximum values. The lower speed levels can be set at any time.


### Mass m as a function of speed level v with parallel kit, horizontal mounting position for EPCS-BS-60-12P



Note:

The lines represent the maximum values. The lower speed levels can be set at any time.


### Mass m as a function of speed level v with parallel kit, vertical mounting position for EPCS-BS-32-3P



Note:


The lines represent the maximum values. The lower speed levels can be set at any time.

## Datasheet

Mass  $m$  as a function of speed level  $v$  with parallel kit, vertical mounting position for EPSCS-BS-32-8P


## Note:

The lines represent the maximum values. The lower speed levels can be set at any time.

Mass  $m$  as a function of speed level  $v$  with parallel kit, vertical mounting position for EPSCS-BS-45-3P

## Note:

The lines represent the maximum values. The lower speed levels can be set at any time.


Mass  $m$  as a function of speed level  $v$  with parallel kit, vertical mounting position for EPSCS-BS-45-10P

## Note:

The lines represent the maximum values. The lower speed levels can be set at any time.

## Datasheet


### Mass m as a function of speed level v with parallel kit, vertical mounting position for EPCS-BS-60-5P



Note:

The lines represent the maximum values. The lower speed levels can be set at any time.


### Mass m as a function of speed level v with parallel kit, vertical mounting position for EPCS-BS-60-12P





Note:

The lines represent the maximum values. The lower speed levels can be set at any time.

### Positioning time t as a function of speed level v and stroke l with axial kit for EPCS-BS-32-3P




## Datasheet


Positioning time  $t$  as a function of speed level  $v$  and stroke  $l$  with axial kit for EPSCS-BS-32-8PPositioning time  $t$  as a function of speed level  $v$  and stroke  $l$  with axial kit for EPSCS-BS-45-3P

## Datasheet



### Positioning time $t$ as a function of speed level $v$ and stroke $l$ with axial kit for EPSCS-BS-45-10P



### Positioning time $t$ as a function of speed level $v$ and stroke $l$ with axial kit for EPSCS-BS-60-5P




## Datasheet


Positioning time  $t$  as a function of speed level  $v$  and stroke  $l$  with axial kit for EPSCS-BS-60-12PPositioning time  $t$  as a function of speed level  $v$  and stroke  $l$  with parallel kit for EPSCS-BS-32-3P

## Datasheet



### Positioning time $t$ as a function of speed level $v$ and stroke $l$ with parallel kit for EPCS-BS-32-8P





### Positioning time $t$ as a function of speed level $v$ and stroke $l$ with parallel kit for EPCS-BS-45-3P



## Datasheet


Positioning time  $t$  as a function of speed level  $v$  and stroke  $l$  with parallel kit for EPSCS-BS-45-10PPositioning time  $t$  as a function of speed level  $v$  and stroke  $l$  with parallel kit for EPSCS-BS-60-5P

## Datasheet

Positioning time  $t$  as a function of speed level  $v$  and stroke  $l$  with parallel kit for EPSCS-BS-60-12PFeed force  $F$  as a function of force level  $F1$ 

The force is controlled and evaluated by regulating the motor current. Depending on the mechanism of the drive, a linear force can be determined from the level of current measured. The target is set as a percentage of the rated motor current and may differ from the actual force at the electric cylinder. At the lower force levels, the frictional force of the drive system may be greater than the set feed force and may result in the drive system coming to a standstill.

## Combinations between axis ELGC, ELGS, mini slides EGSC-BS, EGSS-BS, electric cylinders EPCC, EPSCS and guide axis ELFC



Mounting options with profile mounting EAHF-L2-...-P-D

- Mounting option: Base axis with next smaller assembly axis

1. Base axis:

Product: ELGC, ELGS, ELFC

For size 32, 45, 60, 80


2. Assembly axis:

Product: ELGC, ELGS, EGSC, EGSS, EPCC, EPSCS, ELFC

For size 25, 32, 45, 60

## Datasheet

## Combinations between axis ELGC, ELGS, mini slides EGSC-BS, EGSS-BS, electric cylinders EPCC, EPSCS and guide axis ELFC



Mounting options with angle kit EHAA-D-L2-...-AP

- Mounting option: Base axis with next smaller assembly axis

1. Base axis:

Product: ELGC, ELGS, ELFC


For size 32, 45, 60, 80

2. Assembly axis:

Product: ELGC, ELGS, EGSC, EGSS, EPCC, EPSCS, ELFC

For size 25, 32, 45, 60

## Combinations between axis ELGC, ELGS, mini slides EGSC-BS, EGSS-BS, electric cylinders EPCC, EPSCS and guide axis ELFC



Mounting options with adapter kit EHAA-D-L2

- Mounting option: Base axis with the same size assembly axis

- Mounting option: Base axis with height compensation for the next smaller assembly axis

- When motors are mounted using parallel kits, interfering contours may occur. In this case, the adapter plate is required for height compensation

1. Base axis:

Product: ELGC, ELGS, ELFC


For size 32, 45, 60, 80

2. Assembly axis:

Product: ELGC, ELGS, EGSC, EGSS, EPCC, EPSCS, ELFC

Sizes 25, 32, 45, 60, 80

## Combinations between mini slides EGSC-BS, EGSS-BS



Mounting options with direct mounting

- Mounting option: Base axis with the same size assembly axis

1. Base axis:

Product: EGSC, EGSS


For size 25, 32, 45, 60

2. Assembly axis:

Product: EGSC, EGSS

For size 25, 32, 45, 60


## Dimensions



	B1	B2	H1	H2	L1	L2	L3
EPCS-BS-32	42,3	32	81,1	69,9	175,5	65,5	105,5
EPCS-BS-45	42,3	45	82,6	71,4	188,5	65,5	105,5
EPCS-BS-60	56,6	60	97,3	86,1	216,5	73,5	116,5

## Dimensions

## Dimensions – With parallel motor mounting


Download CAD data  [www.festo.com](http://www.festo.com)

	B1	H1	H2	H3	L1	L2
EPCS-BS-32	111	83	72	45	94	90,7
EPCS-BS-45	111	83	72	45	107	90,7
EPCS-BS-60	155	100	90	65	132	107,7

## Dimensions

### Dimensions – Mechanics

Download CAD data [www.festo.com](http://www.festo.com)




## Dimensions

	B1 ±0,15	B2	B3	B4	B5	D1 Ø	D2 Ø	D3 Ø	D4 Ø
EPCS-BS-32	32	24	16	8,1	25,5	25	15,5	—	2
EPCS-BS-45	45	32,5	24	16,5	35	32	16,3	—	3
EPCS-BS-60	60	46,5	30	24	48,5	42	31,4	48	—
	D5 Ø	D6 Ø	D7 Ø	G1	G2	H1 ±0,15	H2	H4	H5
EPCS-BS-32	31	10	21,3	M4	—	34	24	—	4,9
EPCS-BS-45	41	12	26,5	M5	—	45	32,5	—	6,1
EPCS-BS-60	—	16	33,6	M6	M4	60	46,5	30	6,1
	H6 +0,15	KK	L1	L2	L3	L4	L5	L6	L7
EPCS-BS-32	26	M8	82,9	70	16	12,9	5,2	24,2	6
EPCS-BS-45	28,5	M10x1,25	99,9	83	20	16,9	5,7	30,5	6
EPCS-BS-60	36	M12x1,25	116	100	24	16	7,5	39,5	2,5
	L8	L9	L10	T1	T2	W1	=G2	=G3	
EPCS-BS-32	19,9	14,5	2,5	8	—	60°	9	13	
EPCS-BS-45	19,9	14,5	3	10	—	60°	10	16	
EPCS-BS-60	26,9	16,5	—	12	10	—	13	18	

## Dimensions


## Dimensions – Profile mounting EAHF-L2-...-P-S

Download CAD data  [www.festo.com](http://www.festo.com)

		B1	B2	B3	D1 Ø H13	D2 Ø H13	H2	H4	H5	L1
EAHF-L2-25-P-S	EPCS-BS-32	51,4	9,7	42	4,5	8	4,9	4,2	9	19
EAHF-L2-45-P-S	EPCS-BS-45	70,6	12,8	58	5,5	10	6,1	5,5	12,2	19
EAHF-L2-45-P-S	EPCS-BS-60	85,6	12,8	73	5,5	10	6,1	5,5	12,2	19

## Dimensions


## Dimensions – Profile mounting EAHF-L2-...-P

Download CAD data  [www.festo.com](http://www.festo.com)

		B1	B2	B3	D1 ∅ H13	D2 ∅ H13	D3 ∅	H2	H4	H5	L1	L2
EAHF-L2-25-P	EPSCS-BS-32	51,4	9,7	42	4,5	8	4	4,9	4,2	9	53	40
EAHF-L2-45-P	EPSCS-BS-45	70,6	12,8	58	5,5	10	5	6,1	5,5	12,2	53	40
EAHF-L2-45-P	EPSCS-BS-60	85,6	12,8	73	5,5	10	5	6,1	5,5	12,2	53	40

## Dimensions


## Dimensions – Flange mounting EAHH

Download CAD data  [www.festo.com](http://www.festo.com)

	B1	B2	B3	B4	D1 Ø	H1	H2	H3	L1	L2	L3	L4	=C1
EAHH-P2-32	70	58	16	42	5,5	39	31	20	38	20	30	2,5	2,5
EAHH-P2-45	100	85	24	61	6,6	54,5	48	35	42	20	30	4	2,5
EAHH-P2-60	120	103	30	76	9	69	58	42	52	25	40	4	4

## Dimensions


Dimensions – Adapter kit EAHA

Download CAD data  [www.festo.com](http://www.festo.com)

	B1	B2	B3	D1 Ø	H1	H2	H3	H4	H5	L1	L2	L3	L4	=C1
	±0,2	±0,1				±0,2								
EAHA-P2-32	53	22	16	M5	42	22	37	18	2,5	64	20	30	4	2,5
EAHA-P2-45	61	32,5	24	M6	54	32,5	49	22,5	4	68	20	30	6	2,5
EAHA-P2-60	76	38	30	M6	69,5	38	61	30	4	87	25	40	6	4

## Dimensions


## Dimensions – Swivel mounting EAHS

Download CAD data  [www.festo.com](http://www.festo.com)

	B1	B2	B3	B4	B5	D1 Ø e9	H1	H2	L1	L2	=C1
			±0,1								
EAHS-P2-32	68	57	16	42	2,5	8	32	23,5	30	20	2,5
EAHS-P2-45	98	83	24	62	4	12	44,5	29,5	30	20	2,5
EAHS-P2-60	118	100	30	76	4	16	57	39	40	25	4

## Dimensions


## Dimensions – Trunnion support LNZG

Download CAD data  [www.festo.com](http://www.festo.com)

		CR Ø D11	DA Ø H13	FK Ø ±0,1	FN	FS	H1	HB Ø H13	KE	NH	TH	UL ±0,2
LNZG-16	EPCS-BS-32	8	8	10	20	7,5	11	4,5	4,6	13	20	30
LNZG-32	EPCS-BS-45	12	11	15	30	10,5	15	6,6	6,8	18	32	46
LNZG-40/50	EPCS-BS-60	16	15	18	36	12	18	9	9	21	36	55

## Dimensions


## Dimensions – Swivel flange SNCS

Download CAD data  [www.festo.com](http://www.festo.com)

		CX	DL	E	L	EP	EX	LT	MS	RA	TG	XC
SNCS-32	EPSCS-BS-45	$10^{+0,13}$	22	$45^{+0,2/-0,5}$	3	10,5	14	13	15	14,5	32,5	154,9
SNCS-40	EPSCS-BS-60	$12^{+0,15}$	25	$54_{-0,5}$	3	12	16	16	17	17,5	38	182

## Dimensions


## Dimensions – Swivel flange SNCL

Download CAD data  [www.festo.com](http://www.festo.com)

		CD ∅ H10	E	EW	FL	L	LT	MR	TG	XC
SNCL-16	EPCS-BS-25	6	27,5 <sub>-0,6</sub>	12 <sub>h12</sub>	16	3	10	6	18	115,7
SNCL-20	EPCS-BS-32	8	34,5 <sub>-0,6</sub>	16 <sub>h12</sub>	20	3	14	8	22	133,9
SNCL-32	EPCS-BS-45	10	45 <sub>+0,2/-0,5</sub>	26 <sub>-0,2/-0,6</sub>	22	3	13	10	32,5	154,9
SNCL-40	EPCS-BS-60	12	54 <sub>-0,5</sub>	28 <sub>-0,2/-0,6</sub>	25	3	16	12	38	182

## Dimensions


## Dimensions – Swivel flange SNCB

Download CAD data  [www.festo.com](http://www.festo.com)

		CB	E	EK Ø H10/e8	FL ±0,2	L	LT	MR -0,5	TG	UB h14	XC
SNCB-32	EPSCS-BS-45	26	45+0,2/-0,5	10	22	3	13	8,5	32,5	45	154,9
SNCB-40	EPSCS-BS-60	28	54-0,5	12	25	3	16	12	38	52	182

## Dimensions

## Dimensions – Sensor bracket EAPM-L2

Download CAD data  [www.festo.com](http://www.festo.com)

[1] Proximity switch

	B1	B2	D1	H1	H2	H3	L1	L2
EAPM-L2-SH	5,5	1,3	M4	13,4	6	3	32	25


## Ordering data

Ordering data					
	Size	Spindle pitch	Stroke	Part no.	Type
	32	3 mm/U	50 mm	8118267	EPCS-BS-32-50-3P-A-ST-M-H1-PLK-AA
			100 mm	8118268	EPCS-BS-32-100-3P-A-ST-M-H1-PLK-AA
			150 mm	8118269	EPCS-BS-32-150-3P-A-ST-M-H1-PLK-AA
			200 mm	8118270	EPCS-BS-32-200-3P-A-ST-M-H1-PLK-AA
		8 mm/U	50 mm	8118271	EPCS-BS-32-50-8P-A-ST-M-H1-PLK-AA
			100 mm	8118272	EPCS-BS-32-100-8P-A-ST-M-H1-PLK-AA
			150 mm	8118273	EPCS-BS-32-150-8P-A-ST-M-H1-PLK-AA
			200 mm	8118274	EPCS-BS-32-200-8P-A-ST-M-H1-PLK-AA
	45	3 mm/U	50 mm	8118275	EPCS-BS-45-50-3P-A-ST-M-H1-PLK-AA
			100 mm	8118276	EPCS-BS-45-100-3P-A-ST-M-H1-PLK-AA
			150 mm	8118277	EPCS-BS-45-150-3P-A-ST-M-H1-PLK-AA
			200 mm	8118278	EPCS-BS-45-200-3P-A-ST-M-H1-PLK-AA
			250 mm	8118279	EPCS-BS-45-250-3P-A-ST-M-H1-PLK-AA
			300 mm	8118280	EPCS-BS-45-300-3P-A-ST-M-H1-PLK-AA
		10 mm/U	50 mm	8118281	EPCS-BS-45-50-10P-A-ST-M-H1-PLK-AA
			100 mm	8118282	EPCS-BS-45-100-10P-A-ST-M-H1-PLK-AA
			150 mm	8118283	EPCS-BS-45-150-10P-A-ST-M-H1-PLK-AA
			200 mm	8118284	EPCS-BS-45-200-10P-A-ST-M-H1-PLK-AA
			250 mm	8118285	EPCS-BS-45-250-10P-A-ST-M-H1-PLK-AA
			300 mm	8118286	EPCS-BS-45-300-10P-A-ST-M-H1-PLK-AA
	60	5 mm/U	50 mm	8118287	EPCS-BS-60-50-5P-A-ST-M-H1-PLK-AA
			100 mm	8118288	EPCS-BS-60-100-5P-A-ST-M-H1-PLK-AA
			150 mm	8118289	EPCS-BS-60-150-5P-A-ST-M-H1-PLK-AA
			200 mm	8118290	EPCS-BS-60-200-5P-A-ST-M-H1-PLK-AA
			250 mm	8118291	EPCS-BS-60-250-5P-A-ST-M-H1-PLK-AA
			300 mm	8118292	EPCS-BS-60-300-5P-A-ST-M-H1-PLK-AA
			350 mm	8118293	EPCS-BS-60-350-5P-A-ST-M-H1-PLK-AA
			400 mm	8118294	EPCS-BS-60-400-5P-A-ST-M-H1-PLK-AA
	12 mm/U	5 mm/U	50 mm	8118295	EPCS-BS-60-500-5P-A-ST-M-H1-PLK-AA
			100 mm	8118296	EPCS-BS-60-50-12P-A-ST-M-H1-PLK-AA
			150 mm	8118297	EPCS-BS-60-100-12P-A-ST-M-H1-PLK-AA
			200 mm	8118298	EPCS-BS-60-150-12P-A-ST-M-H1-PLK-AA
			250 mm	8118299	EPCS-BS-60-200-12P-A-ST-M-H1-PLK-AA
			300 mm	8118300	EPCS-BS-60-250-12P-A-ST-M-H1-PLK-AA
			350 mm	8118301	EPCS-BS-60-300-12P-A-ST-M-H1-PLK-AA
			400 mm	8118302	EPCS-BS-60-350-12P-A-ST-M-H1-PLK-AA
			500 mm	8118303	EPCS-BS-60-400-12P-A-ST-M-H1-PLK-AA
			500 mm	8118304	EPCS-BS-60-500-12P-A-ST-M-H1-PLK-AA

Ordering information – Modular product system				
	Size	Stroke	Part no.	Type
	32	25 ... 200 mm	8118264	EPCS-BS-32-
	45	25 ... 300 mm	8118265	EPCS-BS-45-
	60	25 ... 500 mm	8118266	EPCS-BS-60-

## Peripherals

### Peripherals overview



Type/order code	Description	→ Link
[1] Electric cylinder unit EPCS-BS	Electric drive	<a href="#">epcs</a>
[2] Sensor bracket EAPM-L2	For mounting the proximity switches on the axis. The proximity switches can only be mounted using the sensor bracket.	48
[3] Proximity switches SMT-8M	Magnetic proximity switches, for T-slot	48
[4] IO-Link® master USB CDSU-1	For easy use of the electric cylinder unit with IO-Link®	49
[5] Adapter NEFC-M12G8	<ul style="list-style-type: none"> <li>• Connection between motor and IO-Link® master</li> <li>• Only recommended for use with IO-Link® Port class A master</li> </ul>	49
[6] Supply cable NEBL-T12	For connecting the load and logic supply	49
[7] Connecting cable NEBC-M12	For connection to a controller	50
[8] Axial kit	For axial motor mounting More detailed information → <a href="http://www.festo.com/x/electric-motion-sizing">www.festo.com/x/electric-motion-sizing</a> (included in the scope of delivery)	<a href="#">epcs</a>
[9] Parallel kit	For parallel motor mounting More detailed information → <a href="http://www.festo.com/x/electric-motion-sizing">www.festo.com/x/electric-motion-sizing</a> (included in the scope of delivery)	<a href="#">epcs</a>
[10] Swivel flange SNCB	For parallel motor mounting, for spherical bearing	46
[11] Clevis foot LBN	For parallel motor mounting, for spherical bearing	46
[12] Clevis foot LBG/LBG-...-R3	For parallel motor mounting, for spherical bearing	47
[13] Swivel flange SNCL	With parallel motor mounting	46
[14] Swivel flange SNCS/CRSNCS/SNCS-...-R3	With parallel motor mounting	46
[15] Adapter kit EAHA-P2	<ul style="list-style-type: none"> <li>- For mounting the swivel flange and trunnion flange on the front</li> <li>- Can only be mounted on the rear in conjunction with parallel kit EAMM-U</li> </ul>	45
[16] Slot nut ABAN	For mounting the electric cylinder unit	48
[17] Profile mounting EAHF-L2-P	<ul style="list-style-type: none"> <li>- For mounting the axis on the side of the profile</li> <li>- The hole in the middle allows the profile mounting to be attached to the mounting surface</li> </ul>	45
[18] Profile mounting EAHF-L2-P-S	For mounting the axis on the side of the profile	45
[19] Trunnion support LNZG	For cylinders with trunnion mounting	45
[20] Swivel mounting EAHS-P2	Position freely selectable along the cylinder length	45
[21] Flange mounting EAHH-P2	<ul style="list-style-type: none"> <li>- For mounting the electric cylinder via the profile</li> <li>- Position within the cylinder length freely selectable</li> </ul>	45
[22] Adapter kit EAHA-P2	<ul style="list-style-type: none"> <li>- For mounting the swivel flange and trunnion flange on the front</li> <li>- Can only be mounted on the rear in conjunction with parallel kit EAMM-U</li> </ul>	45
[23] Self-aligning rod coupler FK/CRFK	To compensate for radial and angular deviations	47
[24] Rod clevis SG/CRSG	Allows a swivelling movement of the cylinder in one plane	47
[25] Coupling piece KSG	To compensate for radial deviations	47
[26] Rod eye SGS/CRSGS	With spherical bearing	47
[27] Right angle clevis foot LQG	For rod eye SGS	46

## Peripherals

Accessories		→ Link
Type/order code	Description	
[28] Rod clevis SGA	For swivelling cylinder mounting	<a href="#">47</a>
[29] Clevis foot LBG/LBG-...-R3	For parallel motor mounting, for spherical bearing	<a href="#">47</a>
[30] Guide unit EAGF	For protecting electric cylinders against rotation at high torque loads	<a href="#">48</a>

## Accessories


## Profile mounting EAHF-L2-....-P-S

	Description	Material plate	Note on materials	Product weight	Part no.	Type
	For size 32	Anodised wrought aluminum alloy	RoHS-compliant	4 g	5183153	EAHF-L2-25-P-S
	For size 45, 60			6 g	5184133	EAHF-L2-45-P-S


## Profile mounting EAHF-L2-....-P

	Description	Material plate	Note on materials	Product weight	Part no.	Type
	For size 32	Anodised wrought aluminum alloy	RoHS-compliant	19 g	4835684	EAHF-L2-25-P
	For size 45, 60			35 g	4835728	EAHF-L2-45-P

## Flange mounting EAHH

	Description	Note on materials	Product weight	Part no.	Type
	For size 32	RoHS-compliant	80 g	5126157	EAHH-P2-32
	For size 45		185 g	5126669	EAHH-P2-45
	For size 60		320 g	5127005	EAHH-P2-60


## Adapter kit EAHA

	Description	Note on materials	Product weight	Part no.	Type
	For size 32	RoHS-compliant	165 g	5173020	EAHA-P2-32
	For size 45		340 g	5172353	EAHA-P2-45
	For size 60		560 g	5173082	EAHA-P2-60

## Swivel mounting EAHS

	Description	Note on materials	Product weight	Part no.	Type
	For size 32	RoHS-compliant	75 g	5125041	EAHS-P2-32
	For size 45		165 g	5125167	EAHS-P2-45
	For size 60		305 g	5125281	EAHS-P2-60

## Trunnion support LNZG


	Description	Material mounting	Note on materials	Product weight	Part no.	Type
	For size 32	Wrought aluminum alloy	RoHS-compliant	26 g	1434912	LNZG-16
	For size 45			83 g	32959	LNZG-32
	For size 60			129 g	32960	LNZG-40/50

## Accessories


## Swivel flange SNCS

	Description	Material mounting	Note on materials	Product weight	Part no.	Type
	For size 45	Die-cast aluminum	RoHS-compliant	86 g	174397	SNCS-32
	For size 60			122 g	174398	SNCS-40


## Swivel flange SNCL

	Description	Material mounting	Note on materials	Product weight	Part no.	Type
	For size 32	Wrought aluminum alloy	RoHS-compliant	38 g	537792	SNCL-20
	For size 45			71 g	174404	SNCL-32
	For size 60			95 g	174405	SNCL-40

## Swivel flange SNCB

	Description	Material mounting	Note on materials	Product weight	Part no.	Type
	For size 45	Die-cast aluminum	RoHS-compliant	103 g	174390	SNCB-32
	For size 60			155 g	174391	SNCB-40

## Clevis foot transverse LQG


	Description	Material mounting	Note on materials	Product weight	Part no.	Type
	For size 45	Stainless steel casting	RoHS-compliant	301 g	31768	LQG-32
	For size 60			369 g	31769	LQG-40

## Clevis foot LBN

	Description	Material mounting	Note on materials	Product weight	Part no.	Type
	For size 32	Steel, Galvanised	RoHS-compliant	84 g	6059	LBN-20/25
	For size 45			110 g	195860	LBN-32
	For size 60			191 g	195861	LBN-40

## Accessories


## Clevis foot LBG

	Description	Material mount-ing	Note on materi-als	Product weight	Part no.	Type
	For size 45	Stainless steel casting	RoHS-compliant	220 g	31761	LBG-32
	For size 60			300 g	31762	LBG-40


## Rod eye SGS

	Description	Material housing	Note on materi-als	Product weight	Part no.	Type
	For size 32	Galvanised steel	RoHS-compliant	54 g	9255	SGS-M8
	For size 45			88 g	9261	SGS-M10X1,25
	For size 60			130 g	9262	SGS-M12X1,25


## Self-aligning rod coupler FK

	Description	Material housing	Note on materi-als	Product weight	Part no.	Type
	For size 32	Galvanised steel	RoHS-compliant	56 g	2062	FK-M8
	For size 45			236 g	6140	FK-M10X1,25
	For size 60			245 g	6141	FK-M12X1,25


## Coupling piece KSG

	Description	Material mount-ing	Note on materi-als	Product weight	Part no.	Type
	For size 45	Steel, Galvanised	RoHS-compliant	229 g	32963	KSG-M10X1,25
	For size 60			447 g	32964	KSG-M12X1,25

## Rod clevis SG

	Description	Material housing	Note on materi-als	Product weight	Part no.	Type
	For size 32		RoHS-compliant	53 g	3111	SG-M8
	For size 45			103 g	6144	SG-M10X1,25
	For size 60			166 g	6145	SG-M12X1,25

## Rod clevis SGA

	Description	Material housing	Note on materi-als	Product weight	Part no.	Type
	For size 45		RoHS-compliant	129 g	32954	SGA-M10X1,25
	For size 60			222 g	10767	SGA-M12X1,25

## Accessories


## Push-in fitting for sealing air connection

	Description	Material housing	Size of pack	Product weight	Part no.	Type
	For size 25, 32	Brass, nick- el-plated	10	3 g	133004	QSM-M5-4-I-R
	For size 45			3.2 g	133003	QSM-M5-3-I-R
	For size 60			8.9 g	186266	QSM-G1/8-4-I
				9.5 g	186267	QSM-G1/8-6-I
				13 g	186108	QS-G1/4-6-I
				14 g	186110	QS-G1/4-8-I


## Slot nut ABAN

	Description	Material slot nut	Size of pack	Product weight	Part no.	Type
	For sizes 32, 45	Steel	2	5 g	8169987	ABAN-3-3M3-30-M-P2
	For size 60			18 g	8169988	ABAN-5-3M5-40-M-P2

## Guide unit EAGF


	Description	Stroke	Ambient temper- ature	Degree of protec- tion	Part no.	Type
	For size 32	1 ... 200 mm	0 ... 60 °C	IP40	8158030	EAGF-P2-KF-32-
		50 mm			8158032	EAGF-P2-KF-32-50
		100 mm			8158029	EAGF-P2-KF-32-100
		150 mm			8158027	EAGF-P2-KF-32-150
		200 mm			8158028	EAGF-P2-KF-32-200
	For size 45	1 ... 300 mm			8158133	EAGF-P2-KF-45-
		50 mm			8158131	EAGF-P2-KF-45-50
		100 mm			8158123	EAGF-P2-KF-45-100
		150 mm			8158125	EAGF-P2-KF-45-150
		200 mm			8158127	EAGF-P2-KF-45-200
		300 mm			8158130	EAGF-P2-KF-45-300
	for size 60	1 ... 500 mm			8158150	EAGF-P2-KF-60-
		100 mm			8158138	EAGF-P2-KF-60-100
		150 mm			8158140	EAGF-P2-KF-60-150
		200 mm			8158142	EAGF-P2-KF-60-200
		300 mm			8158031	EAGF-P2-KF-60-300

## Sensor bracket EAPM-L2

	Material sensor bracket	Note on materials	Product weight	Part no.	Type
	Anodised wrought alu- minium alloy	RoHS-compliant	4 g	4759852	EAPM-L2-SH

## Proximity switch SMT for T-slot, magneto-resistive

Link  [smt-8m](#)

	Type of mounting	Switching output	Electrical connec- tion	Cable length	Part no.	Type
	Screw-clamped, Insertable in the slot from above	3-wire N/C con- tact NPN	Open end	2.5 m	8138000	SMT-8M-A-NO-24V-E-2,5-OE
		3-wire NPN N/O contact		7.5 m	8138001	SMT-8M-A-NO-24V-E-7,5-OE
		3-wire PNP N/C contact		2.5 m	574338	SMT-8M-A-NS-24V-E-2,5-OE
	Plug M8, A-coded	3-wire PNP N/O contact	Plug M8, A-coded	0.3 m	574339	SMT-8M-A-NS-24V-E-0,3-M8D
		3-wire N/C con- tact	Open end	7.5 m	574340	SMT-8M-A-PO-24V-E-7,5-OE
		3-wire N/O con- tact		2.5 m	574335	SMT-8M-A-PS-24V-E-2,5-OE
	Plug M8, A-coded		Plug M8, A-coded	0.3 m	574334	SMT-8M-A-PS-24V-E-0,3-M8D

## Accessories

IO-Link® master USB				Link  cdsu	
	Description	Part no.	Type		
	For using the unit with IO-Link®, an external power supply plug is also required (not included in the scope of delivery)	8091509	CDSU-1		

Adapter NEFC						
	Electrical connection 1, connector system	Electrical connection 2, connector system	Electrical connection 2, number of connections/cores	Cable length <sup>1)</sup>	Part no.	Type
	M12x1, A-coded to EN 61076-2-101	M12x1, A-coded to EN 61076-2-101	5	0.3 m	8080777	NEFC-M12G8-0.3-M12G5-LK

1) Connection between the motor and the IO-Link® master

Supply cables NEBL, straight						
	Electrical connection 1, connector system	Electrical connection 2, connector system	Electrical connection 2, number of connections/cores	Cable length	Part no.	Type
	M12x1, T-coded according to EN 61076-2-111	Open end	4	2 m	8080790	NEBL-T12G4-E-2-N-LE4
				5 m	8080791	NEBL-T12G4-E-5-N-LE4
				10 m	8080792	NEBL-T12G4-E-10-N-LE4
				15 m	8080793	NEBL-T12G4-E-15-N-LE4

Supply cables NEBL, angled						
	Electrical connection 1, connector system	Electrical connection 2, connector system	Electrical connection 2, number of connections/cores	Cable length	Part no.	Type
	M12x1, T-coded according to EN 61076-2-111	Open end	4	2 m	8080778	NEBL-T12W4-E-2-N-LE4
				5 m	8080779	NEBL-T12W4-E-5-N-LE4
				10 m	8080780	NEBL-T12W4-E-10-N-LE4
				15 m	8080781	NEBL-T12W4-E-15-N-LE4

Connecting cables NEBC, straight						
	Electrical connection 1, connector system	Electrical connection 2, connector system	Electrical connection 2, number of connections/cores	Cable length	Part no.	Type
	M12x1, A-coded to EN 61076-2-101	M12x1, A-coded to EN 61076-2-101	8	2 m	8080782	NEBC-M12G8-E-2-N-M12G8
				5 m	8080783	NEBC-M12G8-E-5-N-M12G8
				10 m	8080784	NEBC-M12G8-E-10-N-M12G8
				15 m	8080785	NEBC-M12G8-E-15-N-M12G8
				2 m	8094480	NEBC-M12G8-E-2-N-B-LE8
				5 m	8094477	NEBC-M12G8-E-5-N-B-LE8
				10 m	8094482	NEBC-M12G8-E-10-N-B-LE8
				15 m	8094475	NEBC-M12G8-E-15-N-B-LE8

## Accessories

## Connecting cables NEBC, angled

	Electrical connection 1, connector system	Electrical connection 2, connector system	Electrical connection 2, number of connections/cores	Cable length	Part no.	Type
	M12x1, A-coded to EN 61076-2-101	M12x1, A-coded to EN 61076-2-101	8	2 m	<b>8080786</b>	NEBC-M12W8-E-2-N-M12G8
				5 m	<b>8080787</b>	NEBC-M12W8-E-5-N-M12G8
				10 m	<b>8080788</b>	NEBC-M12W8-E-10-N-M12G8
				15 m	<b>8080789</b>	NEBC-M12W8-E-15-N-M12G8
		Open end		2 m	<b>8094476</b>	NEBC-M12W8-E-2-N-B-LE8
				5 m	<b>8094478</b>	NEBC-M12W8-E-5-N-B-LE8
				10 m	<b>8094481</b>	NEBC-M12W8-E-10-N-B-LE8
				15 m	<b>8094479</b>	NEBC-M12W8-E-15-N-B-LE8